Weibonuo Communication MIMO Outdoor Small Cell ±45°

10/11dBi 698-2700MHz 2x2 Stadium Antenna

Model: WBN-SC6927X11i65A

Applications

- Supporting 2G/3G/4G LTE/ WLAN network
- 2 Typically used in outdoor distribution of signal coverage
- 1 Improves outdoor wireless network coverage and capacity
- Outdoor wireless networks and Cellular networks

Features

- Low PIM -150dBc @ 2 x 43dBm
- 2 Low VSWR at 1.5
- High quality PVC radome with plastic nut for easy installation
- Attractive, compact design and form factor ideal for Indoor distributor antenna system




Ordering Information

Part Number	3rd Order IMD Standard	Descriptions
WBN-SC6927X011i65A	-153dBc @ 2 x 43dBm (Connector Direct from Bottom)	N-Female Connector
WBN-SC6927X011i65A/4310		4.3–10 Female Connector
WBN-SC6927X011i65A/716D		7/16 DIN Female Connector

^{*} We provide antenna customization on different 3rd order intermodulation (PIM) and connector types, please let us know your requirements

Antenna Patterns



Electrical Specifications

Frequency Range	698-960MHz
	1710-2700MHz
Gain (Typ)	10±1dBi @ 698-960MHz
	11±1dBi @ 1710-2700MHz
PIM, 3rd Order, -dBc (Max)	<-150dBc
Polarization	±45°
VCMD (T)	≤ 1.8 @ 698-960MHz
VSWR (Typ)	≤ 1.5 @ 1710-2700MHz
Horizontal Beamwidth	65±5°
Vertical Beamwidth	30±5°
Isolation	≥25±1dB
Front-to-Back Ratio	≥20dB
Electrical Downtilt	0°
Impedance	50 Ohm
Max. Input Power	100 Watts
Lightning Protection	DC Grounded

Mechanical Specifications

Connector	4.3–10 Female x 2 Ports
Weight	3.8 Kg
Dimensions	600 x 285 x 130 mm
Packing Dimensions	TBD
Radome Material	UPVC
Radome Color	Grey
Rated Wind Velocity	55m/s
Operational Humidity	10-95%
Operating Temperature	-40°C to +60°C
Mounting Hardware	Ф35 ~ Ф65
Mechanical Tilt	0-10°

^{*} The products and specifications described in this document are subject to change without notice.

Enabling communications, anywhere, everywhere.

We listen and answer to your needs with our experience and capability in the industry

www.weibonuo.com

Visit our website or contact our representative for more information.







