

CLAMP SERIES

SDC型竖吊钢板起重钳

SV PLUS VERTICAL LIFTING CLAMP

用途:钢板的竖直吊运。 载荷范围:0~30吨

特点:1、采用低碳优质合金钢制造。

2、以单只试验为额定载荷,最大工作载荷为2倍,吊装作业中单只或二只

配套使用。

3、只能同时吊运一块钢板,禁止层叠吊运,吊运过程中不得碰撞被吊物。 起吊时,必须将拉环手柄向上以使弹簧拉紧;卸荷时,将锁紧手柄向下,弹簧放 松后,钳和钢板才能分离。

Applications

Standard **SCD** clamp is design for vertical lifting and turning over of plates, the clamp possesses a safety device by which the lock is not disengaged even if the lifting rope is slackened. This clamp can be applied for a wide range of works which maintains a structure for safety against ground-touching shocks of the loads.

Technical Specialities

Benefits

- 1.Long product life
- 2.Meets standard BS EN13155
- 3. Guaranteed performance
- 4.Embossed branding
- 5.All forged and heat treated parts
- 6. Safety and reliability with individual serial number
- 7. Easily disassembled and reassembled
- 8.Permanent PI code for good traceability

Working fields


- *Shipyards
- *Subway sites
- *Construction sites
- *Metal production workshop
- 1.Max. load: 1~5 tons Range
- 2.Jaw Opening: 0~50mm
- 3. Safety factor: 6 times
- 4. Safety latch mechanism


Subject to rigorous WORK quality approval Inspection Procedures

- *Vertical lifting of flat plates
- *Turning over of flat plates
- *Lifting of shaped steels



Model: SDC





SDC型竖吊钢板起重钳参数:

SPECIFICATION

型号 Item No.	额定起重量 WII (t)	钳口宽度 Jaw opening (mm)	主要尺寸 Dimensions(mm)										净重 Net Weight
			Α	В	С	D	E	F	G	н	1	J	(kg)
SDC1	1	0~22	24	32	123	46	22	274	29	142	52	12	4.5
SDC2	2	0~32	35	42	152	50	25	302	38	188	63	14	7.0
SDC3	3	0~36	38	48	170	58	35	360	45	203	68	19	11.0
SDC5	5	0~50	52	54	220	62	58	458	58	236	76	20	17.2